



CADENCE™ DOOR PULLS / DP7550 SERIES

PRODUCT DATA





CADENCE™ DOOR PULLS / DP7550 SERIES

PRODUCT DATA

Cadence Door Pulls make it easy to carry a design theme throughout an installation. As part of the Cadence collection, the door pulls, along with the line's coordinating cabinet pulls, are cast of solid stainless steel or bronze. Sophisticated finishing techniques accentuate each pull's fluid curves and ensure an inviting, comfortable grip.

PRODUCT DETAILS

The following applies to all Cadence Door Pull designs shown on page 2.

MATERIAL & FINISH			MAINTENANCE
Stainless Steel	US32	Polished Stainless Steel	Cadence Door Pulls are well-suited for interior or exterior use. Regular maintenance will help ensure the lasting beauty of each pull. For more information, please refer to the Door Hardware Care & Maintenance document found on our website.
	US32D	Satin Stainless Steel	
	SSS	Stippled Stainless Steel	
Bronze	US9	Polished Bronze	
	US10	Satin Bronze	
	SBR	Stippled Bronze	
	US10B	Oil-Rubbed Bronze	
	S10	Stippled Oil-Rubbed Bronze	
WSB	Combination Wrought Oil-Rubbed Bronze & Stippled Oil-Rubbed Bronze		

MOUNTING OPTIONS

Cadence Door Pulls are installed using Mounting System "B" as shown below. To ensure a secure installation, a thread-locking adhesive such as Loctite® is recommended. For more information, refer to the Door Pull Installation Manual on our website.

MOUNTING SYSTEM "B"

B1	B2	B3	B4*	B5	B6
Single mount	Single mount	Concealed single mount	Concealed single mount	Back-to-back mount	Back-to-back mount
Solid wood core or hollow metal door with through bolt.	Tempered glass, solid wood core or hollow metal door with end cap purchased separately.	Hollow metal door with Rota-Lok and customer's reinforcement.	Solid wood core door with threaded insert and Rota-Lok.	Solid wood core or hollow metal door with Rota-Lok.	Tempered glass door with Rota-Lok.

"L" CONFIGURATION

	<p>Comprised of two door pulls, one end of each pull is mounted back-to-back, while the remaining ends are single-mounted. Mounting options are dependent on the door type and door pulls being utilized.</p> <p>For additional information, refer to the Door Pull Mounting Options guide or Door Pull Installation Manual on our website.</p>
--	---

*Forms+Surfaces offers but does not recommend concealed mounting on wood doors. Frequent or heavy use can compromise the integrity of this mounting.

HOW TO SPECIFY

Provide model number, center-to-center (c.c.) dimension, quantity, metal and finish, mounting option, and door material and thickness. Refer to the standalone Door Hardware Price List on our website for list pricing.



CADENCE™ DOOR PULLS / DP7550 SERIES

PRODUCT DATA

DESIGN OPTIONS

<p>DP7551-12</p>	<p>DP7551-20</p>	<p>DP7552-20</p>	<p>DP7553-12</p>
<p>DP7553-20</p>	<p>DP7555-12</p>	<p>DP7558-20 (LEFT)</p>	<p>DP7559-20 (RIGHT)</p>