

PROJECT NAME: \_\_\_\_\_

DATE: \_\_\_\_\_

JOB LOCATION: \_\_\_\_\_

SPECIFIER: \_\_\_\_\_

PLEASE USE ADOBE READER OR ADOBE ACROBAT TO FILL OUT AND SAVE FORM. USING OTHER PROGRAMS COULD RESULT IN UNSAVED DATA.

APPLICATIONS

If you select a Forms+Surfaces System, please skip the Project Details, Lite Descriptions and Glass Characteristics sections.

Forms+Surfaces Systems

☐ LEVELr Wall Cladding System

☐ LEVELr Column System

☐ LEVELe Wall Cladding System

☐ LEVELe Column System

☐ LEVELe Elevator Interiors

☐ LEVELc-2000 Elevator Interiors

☐ Glass Doors

☐ Stile & Rail Doors

☐ LightPlane Panels (View only)

Other Applications\*

☐ Loose Lite(s)

☐ Other: \_\_\_\_\_

\*For Other Applications, please fill out all sections.

PROJECT DETAILS

Please choose **one** option from each category.

Installation Type

☐ Captured Top & Bottom Only

☐ Fully Framed

☐ Mounted to a Solid Substrate

☐ Curtain Wall/IGU

☐ Post Mounted with Holes

☐ Water Feature

Glass Thickness

☐ 5/16" (7.7 mm)

☐ 7/16" (11.1 mm)

☐ 9/16" (13.7 mm)

Environment

☐ Interior, Standard Humidity

☐ Interior, High Humidity

☐ Exterior, Exposed Setting

☐ Exterior, Covered Setting

Lighting Conditions

☐ Natural

☐ Backlit

☐ Spotlight

☐ Other (please provide details):  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

LITE DESCRIPTION

Description (include part number, if available)	Quantity	Size (width x height)
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

GLASS CHARACTERISTICS

Please choose **one** option from each category.

Safety Standards

☐ Annealed

☐ Tempered\*

☐ Heat Strengthened\*\*

Profile

☐ Flat

☐ Curved (please attach drawing)

\*Tempering is required for load bearing holes and cutouts. Please note that 5/16" laminated glass can only be tempered to a max of 47" x 80".  
\*\*Heat strengthening is recommended for glass over 50 square feet.

PROCESSING REQUIREMENTS

Please choose **all** options that apply and provide detail as needed.

Edges

Seamed Edges

☐ Top

☐ Bottom

☐ Left Side

☐ Right Side

Flat Machine Polished Edges

☐ Top

☐ Bottom

☐ Left Side

☐ Right Side

Cuts

Notches\*

☐ Yes

☐ No

Internal Cutouts\*

☐ Yes

☐ No

Pattern Cuts\*

☐ Yes

☐ No

Holes\*

☐ Yes

☐ No

ANSI

ANSI logo on glass\*\*

☐ Yes

☐ No

ANSI logo type

☐ American

☐ Canadian

ANSI logo placement

☐ Standard

☐ Custom\*\*\*

*\*If yes, please attach drawing.*  
*\*\*ANSI logo is required for elevator interiors.*  
*\*\*\*If ANSI logo placement is custom, please provide details.*

DESIGN CHARACTERISTICS

Please choose **one** option from each category.

Configuration

☐ View

☐ Reflect

Finish

☐ Standard

☐ Pearlex+

☐ Standard / Pearlex+\*

\*One side Standard / one side Pearlex+ (View configuration only).

SLAB OPTIONS

Please choose **one** slab option below. To select slabs and configure your ViviStone design, visit the ViviStone Virtual Quarry at [www.virtualquarry.com](http://www.virtualquarry.com).

☐ Cream Onyx A-1

☐ Cream Onyx A-2

☐ Cream Onyx A-3

☐ Cream Onyx B-4

☐ Cream Onyx B-5

☐ Cream Onyx B-6













☐ Cream Onyx C-7

☐ Cream Onyx C-8

☐ Cream Onyx C-9


☐ Cream Onyx D-10


☐ Cream Onyx D-11

☐ Cream Onyx D-12













NOTES

Please send completed forms to [sales@forms-surfaces.com](mailto:sales@forms-surfaces.com) or contact us at 800.451.0410 with any questions.