### **DIVISION 12 00 00**

### **FURNISHINGS**

SECTION 12 93 00 SECTION 12 93 43

SITE FURNISHINGS

PACIFICA BENCH

SITE SEATING AND TABLES SECTION 12 93 43.13 SITE SEATING

### Part 1 General

### 01. Summary

# A. Section Includes:

- 1. Eight-foot backed bench, full back, surface mount, steel frame, FSC 100% Jatoba hardwood slats.
- 2. Eight-foot backed bench, full back, freestanding, steel frame, FSC 100% Jatoba hardwood
- 3. Eight-foot backed bench, short back, surface mount, steel frame, FSC 100% Jatoba hardwood
- 4. Eight-foot backed bench, short back, freestanding, steel frame, FSC 100% Jatoba hardwood slats.
- 5. Eight-foot backless bench, surface mount, steel frame, FSC 100% Jatoba hardwood slats.
- 6. Twelve-foot backed bench, full back, surface mount, steel frame, FSC 100% Jatoba hardwood slats.
- 7. Twelve-foot backed bench, full back, freestanding, steel frame, FSC 100% Jatoba hardwood slats.
- 8. Twelve-foot backed bench, short back, surface mount, steel frame, FSC 100% Jatoba hardwood slats.
- 9. Twelve-foot backed bench, short back, freestanding, steel frame, FSC 100% Jatoba hardwood slats.
- 10. Twelve-foot backless bench, surface mount, steel frame, FSC 100% Jatoba hardwood slats.

# 02. Submittals

- A. Provide submittals in accordance with Section 01 33 00 Submittal Procedures.
- B. Product data:
  - 1. Manufacturer's standard product literature.
  - 2. Shop drawings.
  - 3. Installation instructions.
  - 4. Maintenance instructions.
- C. Submit powdercoat finish samples for approval.

## 03. Quality Assurance

- A. Manufacturer Qualifications:
  - 1. Minimum 15 years experience in the manufacture of site seating.
  - 2. Forest Stewardship Council ("FSC") Certified Supplier. Provide manufacturer's FSC certification number.
  - 3. Provide reference list of at least ten major transportation authorities, municipalities, universities, or
    - other high-use public environments currently using site seating fabricated by the manufacturer.

- 04. Delivery, Storage and Handling
  - A. Handle products in accordance with manufacturer's instructions.
  - B. Store products in manufacturer's original packaging until ready for installation.
  - C. Protect products from impacts and abrasion during storage.
- 05. Warranty
  - A. Provide manufacturer's standard warranty:
    - 1. Warranty terms: one year from date of invoice against defects in materials and workmanship.

## Part 2 Products

- 01. Manufacturer
  - A. Basis-of-design product: provide backed and/or backless benches based on the product named:
    - 1. Pacifica Bench by Forms+Surfaces.
    - 2. Manufacturer Contact:

Forms+Surfaces

30 Pine Street

Pittsburgh, PA 15223

phone: 800-451-0410

fax: 412-781-7840

email: sales@forms-surfaces.com website: www.forms-surfaces.com

### B. Benches

- 1. Materials:
  - a. Seat slats and cross members: nominal 1.5" x 2.38" FSC 100% Jatoba hardwood.
  - b. Seat hardware: tensioned joinery and stainless steel spacers.
  - c. Bench frame: welded carbon steel plate.
  - d. Armrests: formed and welded steel.
- 2. Finishes
  - a. Seat slats and cross members: penetrating oil finish.
    - 1) Finish color: Penofin® hardwood formula "Transparent Natural."
  - b. Bench frame & armrests:
    - Undercoat: electrodeposited Zinc per ASTM B-633 with an additional Type II conversion coating.
    - 2) Primer: Zinc-rich primer powdercoat, epoxy resin base.
    - 3) Color coat: Polyester powdercoat (Select one option below):
      - 1. Standard Texture/ Gloss from Forms+Surfaces Powdercoat Chart.
      - 2. Premium Texture from Forms+Surfaces Powdercoat Chart.
      - 3. Custom RAL powdercoat color.
- 3. Dimensions (Select model(s) below):
  - a. Eight-foot backed bench, full back, surface mount: 96" long x 26.7" deep x 32.7" high. Back length 96", seat height 16.5", armrest height 22".

- b. Eight-foot backed bench, full back, freestanding: 96" long x 26.7" deep x 32.7" high. Back length 96", seat height 16.5", armrest height 22".
- c. Eight-foot backed bench, short back, surface mount: 96" long x 26.7" deep x 32.7" high. Back length 68.50", seat height 16.5", armrest height 22".
- d. Eight-foot backed bench, short back, freestanding: 96" long x 26.7" deep x 32.7" high. Back length 68.50", seat height 16.5", armrest height 22".
- e. Eight-foot backless bench, surface mount: 96" long x 15.75" deep x 16" high. Armrest height 22".
- f. Twelve-foot backed bench, full back, surface mount: 144" long x 26.7" deep x 32.7" high. Back length 144", seat height 16.5", armrest height 22".
- g. Twelve-foot backed bench, full back, freestanding: 144" long x 26.7" deep x 32.7" high. Back length 144", seat height 16.5", armrest height 22".
- h. Twelve-foot backed bench, short back, surface mount: 144" long x 26.7" deep x 32.7" high. Back length 96", seat height 16.5", armrest height 22".
- i. Twelve-foot backed bench, short back, freestanding: 144" long x 26.7" deep x 32.7" high. Back length 96", seat height 16.5", armrest height 22".
- j. Twelve-foot backless bench, surface mount: 144" long x 15.75" deep x 16" high. Armrest height 22".
- 4. Mounting (Select one mounting option below, depending on model):
  - a. Freestanding.
  - b. Surface mount. Provide installation hardware when surface mount is specified.

### Part 3 Execution

- 01. Examination
  - A. Verify that substrates are stable and capable of supporting the weight of items covered under this section.
  - B. Verify that substrates have been adequately prepared to securely anchor those items that will be surface
- 02. Installation

mounted.

- A. Install according to the manufacturer's installation instructions.
- B. Install in conformance to applicable ADA guidelines and End User's established Accessibility policies.

# **END OF SECTION**