



SITE FURNISHINGS & LIGHTING

CARE & MAINTENANCE

DISINFECTING NON-POROUS SURFACES

Powdercoated metal, anodized aluminum, Stainless Steel, Fused Metal, metals with Ceramiloc Treatment, acrylic and glass are non-porous surfaces that have been tested and can be successfully disinfected with Simple Green d Pro 3 Plus, a disinfectant, fungicide, virucide, mildewstat, and sanitizer that kills 99.9% of germs.

Per the manufacturer, "Simple Green d Pro 3 Plus has demonstrated effectiveness against viruses similar to SARS-CoV-2 on hard non-porous surfaces. Therefore Simple Green d Pro 3 Plus can be used against SARS-CoV-2 when used in accordance with the directions for use against Human Coronavirus on hard non-porous surfaces. Refer to the CDC website at www.cdc.gov/coronavirus for additional information."

Simple Green d Pro 3 is sold as a concentrate. Dilute to 2 ounces per 1 gallon of water for general use or for use as a disinfectant, fungicide, or virucide. For full instructions, please visit the manufacturer's website at simplegreen.com/products/d-pro-3-plus. Light streaking may occur with some finishes and can be easily removed by rinsing the surface with a small amount of water and drying with a clean microfiber cloth. It is important to use a separate microfiber cloth for water than was used for applying Simple Green d Pro 3.

ROUTINE MAINTENANCE

POWDERCOATED METAL & ANODIZED ALUMINUM

Powdercoated aluminum, cast iron, stainless steel, steel, all other powdercoated metals and anodized aluminum can be cleaned, as needed, using a soft brush or cloth with warm water and a mild detergent. Do not use harsh abrasives, acids or chlorine-based cleaners or cleaning tools containing carbon steel, such as steel wool or wire brushes.

STAINLESS STEEL & FUSED METAL FINISHES

Fingerprints, smudges and more persistent dirt can be removed by using a solution of Simple Green All-Purpose Cleaner and water. We recommend diluting to a 4:1 ratio of water to Simple Green for general cleaning and a 2:1 ratio for set in dirt and oil. Note that Simple Green is sold as a concentrate, both in the spray bottle and 1-gallon container. Spray the diluted Simple Green on a microfiber cloth and wipe the surface until clean. Rinse with water and a clean microfiber cloth for a streak-free finish. Depending on the ratio and amount of Simple Green used, 2-3 rinse cycles may be required. After the last rinse, buff the surface with a dry microfiber cloth. Do not use harsh abrasives, acids or chlorine-based cleaners or cleaning tools containing carbon steel, such as steel wool or wire brushes.

Stainless steel's bright appearance can be maintained by occasional polishing with a soft cloth dipped in common household white vinegar. Commercial products specifically formulated for stainless steel such as Weiman® Stainless Steel Spray or Magic Stainless Steel Cleaner may also be used.

ACRYLIC & GLASS

Acrylic and glass lenses can be cleaned, as needed, using a soft brush or cloth with warm water and a mild detergent. Glass cleaners such as Windex® may also be used. Avoid abrasive cleaners and cleaning tools.

FSC® RECYCLED RECLAIMED CUMARU AND FSC® 100% IPÉ, JATOBA AND CUMARU HARDWOODS

FSC Recycled reclaimed Cumaru and FSC 100% Ipé, Jatoba and Cumaru hardwood slats can be maintained by re-oiling, as needed, with [Penofin® Hardwood Finish](#) in Transparent Natural or similar products. Wood should be re-oiled 3-6 months after installation and again after 10-12 months, or as soon as oil looks depleted. After this time, maintenance needs will be less frequent.

Before applying Penofin Hardwood Finish, wood should be washed with a mild detergent, warm water and soft brush and left to dry for 48 hours. Oil should be shaken well before use. 20-30 minutes after maintenance coat is applied, excess oil should be removed with a clean, dry, nap-free cloth.

FSC® RECYCLED RECLAIMED TEAK HARDWOOD

FSC Recycled reclaimed Teak hardwood slats can be maintained by re-oiling as needed with linseed oil.

Before applying linseed oil, wood should be washed with a mild detergent, warm water and soft brush. Avoid abrasive cleaners and cleaning tools, as well as alcohol, wax and oil-based cleaners. The wood must then be rinsed completely and left to dry for 48 hours before linseed oil application. Apply linseed oil with a paintbrush and immediately wipe any drips or runs with a clean, dry, nap-free cloth. If multiple coats are desired, excess oil must be removed between coats.

FSC® MIXED CREDIT THERMALLY MODIFIED RED OAK

The Thermally Modified Red Oak used in our products is unfinished, which allows the wood's deep brown color to stand out. Over time, the wood will weather to a pewter grey and can be oiled if desired to maintain the deeper brown appearance.

CUSHIONS & SUNBRELLA® FABRIC

Cushions and Sunbrella® fabric covers can be cleaned by brushing off loose dirt and cleaning with water and a mild soap.

GRAPHICS

Use caution when cleaning over graphics. Clean gently with soft brush or nap free cloth with warm water and a mild detergent. Avoid abrasive cleaners and cleaning tools.