



**ALLEGRO™ DOOR PULLS**

PRODUCT DATA





# ALLEGRO™ DOOR PULLS

PRODUCT DATA

Allegro Door Pulls create an elegant opening statement. Available in a variety of shapes and sizes, pulls are cast of solid stainless steel or bronze. Robust finishes enhance each form and add to the visual richness of the collection.

## MATERIALS & FINISHES

## INSTALLATION & MAINTENANCE

STAINLESS STEEL		BRONZE		INSTALLATION	MAINTENANCE
US32	Polished Stainless Steel	US9	Polished Bronze		
US32D	Satin Stainless Steel	US10	Satin Bronze		
SSS	Stippled Stainless Steel	SBR	Stippled Bronze		
		US10B	Oil-Rubbed Bronze		
		S10	Stippled Oil-Rubbed Bronze		

**INSTALLATION**

- Allegro Door Pulls may be single mounted or mounted back-to-back on wood, metal or glass doors.
- Allegro Door Pulls are installed using Mounting System "B". A thread-locking adhesive such as Loctite® is recommended for secure installation. Refer to Mounting Options B1, B2, B3, B4, B5, B6 and B7 shown below for additional information.

**MAINTENANCE**

- Allegro Door Pulls are well-suited for interior or exterior use. Regular maintenance will help ensure the lasting beauty of each pull. For more information, please refer to *Door Hardware Care & Maintenance* found on our website.

## DESIGN OPTIONS

<b>DP7751-12</b>	<b>DP7751-20</b>	<b>DP7753-12</b>	<b>DP7753-20</b>
<b>DP7758-20 (LEFT)</b>	<b>DP7759-20 (RIGHT)</b>		



# ALLEGRO™ DOOR PULLS

PRODUCT DATA

## MOUNTING OPTIONS

<b>B-1</b> Back-to-back mount on wood or metal door with Rota-Lok.	<b>B-2</b> Single mount on glass door with end cap purchased separately.	<b>B-3</b> Back-to-back mount on glass door with Rota-Lok.	<b>B-4</b> Single mount on wood or metal door with through bolt.	<b>*B-5</b> Concealed single mount on wood door with threaded insert and Rota-Lok.	<b>B-6</b> "L" Configuration: Adapt one end of each pull for back-to back mounting with Rota-Lok. Specify "B" mounting for other ends.	<b>B-7</b> Concealed single mount on aluminum frame door with Rota-Lok and customer's reinforcement.
*Forms+Surfaces offers but does not recommend concealed mounting on wood doors. Frequent or heavy use can compromise the integrity of this mounting.						

For more information on mounting Allegro Door Pulls, please refer to the *Hardware Installation Instruction Manual* found on our website.

## LIST PRICING AND ORDERING INFORMATION

Pricing does not include freight. No additional charge for mounting hardware. All pricing is for single units, not pairs.

MODEL	STAINLESS STEEL	BRONZE
DP7701 End Cap; 2" (51mm) dia.	US32, US32D, SSS \$74	US9, US10, SBR, US10B, S10 \$100
DP7751 Straight; 12" (305mm) c.c.	US32, US32D, SSS \$463	US9, US10, SBR, US10B, S10 \$695
DP7751 Straight; 20" (508mm) c.c.	US32, US32D, SSS \$613	US9, US10, SBR, US10B, S10 \$919
DP7753 Offset; 12" (305mm) c.c.	US32, US32D, SSS \$463	US9, US10, SBR, US10B, S10 \$695
DP7753 Offset; 20" (508mm) c.c.	US32, US32D, SSS \$613	US9, US10, SBR, US10B, S10 \$919
DP7758 S-Shape-Left; 20" (508mm) c.c.	US32, US32D, SSS \$613	US9, US10, SBR, US10B, S10 \$919
DP7759 S-Shape-Right; 20" (508mm) c.c.	US32, US32D, SSS \$613	US9, US10, SBR, US10B, S10 \$919

## HOW TO SPECIFY

Provide model number, center-to-center (c.c.) dimension, quantity, metal and finish, mounting option, door material and thickness.