



**CADENCE™ DOOR PULLS**

PRODUCT DATA





# CADENCE™ DOOR PULLS

PRODUCT DATA

Cadence Door Pulls make it easy to carry a design theme throughout an installation. As part of the Cadence collection, the door pulls, along with the line's coordinating cabinet pulls, are cast of solid stainless steel or bronze. Sophisticated finishing techniques accentuate each pull's fluid curves and ensure an inviting, comfortable grip.

## MATERIALS & FINISHES

## INSTALLATION & MAINTENANCE

STAINLESS STEEL		BRONZE		INSTALLATION	MAINTENANCE
US32	Polished Stainless Steel	US9	Polished Bronze		
US32D	Satin Stainless Steel	US10	Satin Bronze		
SSS	Stippled Stainless Steel	SBR	Stippled Bronze		
		US10B	Oil-Rubbed Bronze		
		S10	Stippled Oil-Rubbed Bronze		
		WSB	Combination Wrought Oil-Rubbed Bronze & Stippled Oil-Rubbed Bronze		

**INSTALLATION**

- Cadence Door Pulls may be single mounted or mounted back-to-back on wood, metal or glass doors.
- Cadence Door Pulls are installed using Mounting System "B". A thread-locking adhesive such as Loctite® is recommended for secure installation. Refer to Mounting Options B1, B2, B3, B4, B5, B6 and B7 shown on page 2 for additional information.

**MAINTENANCE**

- Cadence Door Pulls are well-suited for interior or exterior use. Regular maintenance will help ensure the lasting beauty of each pull. For more information, please refer to *Door Hardware Care & Maintenance* found on our website.

## DESIGN OPTIONS

<p>1.125" (29mm) 2.625" (67mm) 12" (305mm) 13" (330mm)</p> <p><b>DP7551-12</b></p>	<p>1.4375" (37mm) 3.1875" (81mm) 20" (508mm) 21.25" (540mm)</p> <p><b>DP7551-20</b></p>	<p>4.0625" (103mm) 3.375" (86mm) 20" (508mm) 21.25" (540mm)</p> <p><b>DP7552-20</b></p>	<p>3" (76mm) 3.0625" (78mm) 12" (305mm) 13" (330mm)</p> <p><b>DP7553-12</b></p>
<p>4.25" (108mm) 3.1875" (81mm) 20" (508mm) 21.25" (540mm)</p> <p><b>DP7553-20</b></p>	<p>6.5" (165mm) 3.125" (79mm) 12" (305mm) 13.25" (337mm)</p> <p><b>DP7555-12</b></p>	<p>3.125" (79mm) 3.1875" (81mm) 20" (508mm) 21.25" (540mm)</p> <p><b>DP7558-20 (LEFT)</b></p>	<p>3.125" (79mm) 3.1875" (81mm) 20" (508mm) 21.25" (540mm)</p> <p><b>DP7559-20 (RIGHT)</b></p>

T 1.800.451.0410 | F 412.385.4715 | www.forms-surfaces.com

**FORMS+SURFACES®**

© 2020 Forms+Surfaces® | All dimensions are nominal. Specifications and pricing subject to change without notice. For the most current version of this document, please refer to our website at www.forms-surfaces.com.



**MOUNTING OPTIONS**

<b>B-1</b> Back-to-back mount on wood or metal door with Rota-Lok.	<b>B-2</b> Single mount on glass door with end cap purchased separately.	<b>B-3</b> Back-to-back mount on glass door with Rota-Lok.	<b>B-4</b> Single mount on wood or metal door with through bolt.	<b>*B-5</b> Concealed single mount on wood door with threaded insert and Rota-Lok.	<b>B-6</b> "L" Configuration: Adapt one end of each pull for back-to back mounting with Rota-Lok. Specify "B" mounting for other ends.	<b>B-7</b> Concealed single mount on aluminum frame door with Rota-Lok and customer's reinforcement.

\*Forms+Surfaces offers but does not recommend concealed mounting on wood doors. Frequent or heavy use can compromise the integrity of this mounting.

For more information on mounting Cadence Door Pulls, please refer to the *Hardware Installation Instruction Manual* found on our website.

**LIST PRICING AND ORDERING INFORMATION**

Pricing does not include freight. No additional charge for mounting hardware. All pricing is for single units, not pairs.

MODEL	STAINLESS STEEL	BRONZE
DT1001 End Cap; 1" (25mm) dia.*	US32, US32D, SSS \$40	US9, US10, SBR, US10B, S10 \$56
DT1201 End Cap; 1.25" (32mm) dia.*	US32, US32D, SSS \$74	US9, US10, SBR, US10B, S10 \$100
DP7551 Straight; 12" (305mm) c.c.	US32, US32D, SSS \$391	US9, US10, SBR, US10B, S10, WSB \$587
DP7551 Straight; 20" (508mm) c.c.	US32, US32D, SSS \$578	US9, US10, SBR, US10B, S10, WSB \$868
DP7552 Double S-Shape; 20" (508mm) c.c.	US32, US32D, SSS \$578	US9, US10, SBR, US10B, S10, WSB \$868
DP7553 Offset; 12" (305mm) c.c.	US32, US32D, SSS \$391	US9, US10, SBR, US10B, S10, WSB \$587
DP7553 Offset; 20" (508mm) c.c.	US32, US32D, SSS \$578	US9, US10, SBR, US10B, S10, WSB \$868
DP7555 C-Shape; 12" (305mm) c.c.	US32, US32D, SSS \$391	US9, US10, SBR, US10B, S10, WSB \$587
DP7558 S-Shape-Left; 20" (508mm) c.c.	US32, US32D, SSS \$578	US9, US10, SBR, US10B, S10, WSB \$868
DP7559 S-Shape-Right; 20" (508mm) c.c.	US32, US32D, SSS \$578	US9, US10, SBR, US10B, S10, WSB \$868

\*Contact Forms+Surfaces Inside Sales to determine the appropriate diameter end cap for specific door pulls.

**HOW TO SPECIFY:**

Provide model number, center-to-center (c.c.) dimension, quantity, metal and finish, mounting option, door material and thickness.