CASTGLASS™ PROFILE MONOLITHIC

			DESIGN	
ROJECT NAME:		DATE: SPECIFIER:		
DB LOCATION:				
PLEASE USE ADOB	SE READER OR ADOBE ACROBAT TO FILL O	UT AND SAVE FORM. USING OTHER PROGRAMS COULD	RESULT IN UNSAVED DATA.	
		APPLICATIONS		
ou select a Forms+Surfaces System, ple	ease skip the Project Details, Lite Descr	riptions and Glass Characteristics sections.		
Forms+Surfaces Systems		Other Applications**		
Glass Doors*		Loose Lite(s)		
Stile & Rail Doors*		Other:		
*Chase 12, Chase 25, and Corduroy are the only textures available for use in Glass Doors and Stile & Rail Doors.		**For Other Applications, please fill out all sections.		
		PROJECT DETAILS		
ase choose one option from each categ	ory.			
stallation Type	Glass Thickness	Environment	Lighting Conditions	
Captured Top & Bottom Only	1/4" (6 mm)	Interior, Standard Humidity	Natural	
Fully Framed	3/8" (10 mm)	Interior, High Humidity	☐ Backlit	
Mounted to a Solid Substrate	1/2" (12 mm)	Exterior, Exposed Setting	Spotlight	
Curtain Wall/IGU		Exterior, Covered Setting	Other (please provide details):	
Post Mounted with Holes				
Water Feature				
		LITE DESCRIPTION		
Description (include part number, if available)		Quantity	Size (width x height)	
	GLA	ASS CHARACTERISTICS		
ase choose one option from each categ	ory.			
fety Standards	Glass Type	Profile		
Monolithic and Tempered*	Clear	Flat		
Laminated and Annealed**	Low Iron	Curved (please attach drawing)		
Laminated and Tempered**	Greytone***			

FORMS+SURFACES®

^{**} Available thicknesses vary by texture. Some textures cannot be laminated. Please consult the Product Data Sheet or call for details.

^{***} Greytone glass is only available with the Chase 12, Chase 25, and Chase 50 textures.

STANDARD TEXTURES

Please choose one texture option below.

Chase 12



Chase 25



Chase 50



Corduroy




Lanto*



Monato*



Sticks*



Taglio *



*Note: These textures may require flanges for installation within a channel or frame.

Please send completed forms to sales@forms-surfaces.com or contact us at 800.451.0410 with any questions.

DESIGN GUIDE

		SURFACE TREATMENT OPTIONS					
Backcoating and sandblasting can be selected together. If no surface treatment is desired, skip this category.							
Backcoated* Transparent Frosted Opaque Color: *Backcoating is not an option with Greytone g			Sandblasted				
		PROCESSING REQUIREMENTS					
Please choose all options that apply and provi	ide detail as needed.						
Kiln Polished Edges	Тор	Bottom	Left Side	Right Side			
Flat Machine Polished Edges	Тор	Bottom	Left Side	Right Side			
Flanges* Flanges Location Notches** Internal Cutouts** Pattern Cuts** Tempering Decal** Holes**	Yes Vertical Yes Yes Yes Yes Yes Yes Yes	No No No					
*Not all textures are available with flanges. Please contact us for details on texture availability. **If yes for any of the above options, please attach drawing.							
NOTES							

FORMS+SURFACES®