

PROJECT NAME: \_\_\_\_\_ DATE: \_\_\_\_\_

JOB LOCATION: \_\_\_\_\_ SPECIFIER: \_\_\_\_\_

PLEASE USE ADOBE READER OR ADOBE ACROBAT TO FILL OUT AND SAVE FORM. USING OTHER PROGRAMS COULD RESULT IN UNSAVED DATA.

**APPLICATIONS**

**Forms+Surfaces Systems\***

- Glass Doors
- LEVELc-2000N Elevator Interiors
- LEVELe Wall System
- LEVELe Elevator System

*\*If you select a Forms+Surfaces System, please skip the Installation Type, Project Details, Lite Descriptions and Glass Characteristics sections.*

**Other Applications\*\***

- Loose Lite(s)
- Other \_\_\_\_\_

*\*\*For Other Applications, please fill out all sections.*

**INSTALLATION TYPE**

- Butt Glazed
- Curtain Wall/IGU
- Mounted Solid Substrate
- Post Mounted with Holes

**PROJECT DETAILS**

*Please choose **one** option from each category.*

**Environment**

- Interior, Standard Humidity
- Interior, High Humidity

**Lighting Conditions**

- Natural
- Backlit
- Spotlight
- Other (please provide details): \_\_\_\_\_

**Glass Thickness**

- 3/8" (9.5 mm)
- 5/8" (15.9 mm)

**LITE DESCRIPTION**

Description (include part number, if available)	Quantity	Size (width x height)
_____	_____	_____
_____	_____	_____
_____	_____	_____

**GLASS CHARACTERISTICS**

*Please choose one option from each category.*

**Safety Standards**

- Annealed
- Tempered\*
- Heat Strengthened\*\*

If Tempered or Heat Strengthened glass is selected, please provide reason:

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

**Profile**

- Flat
- Curved (please attach drawing)

*\*Tempering is required for load bearing holes and cutouts.*

*\*\*Heat strengthening is recommended for glass over 50 square feet.*

**PROCESSING REQUIREMENTS**

*Please choose all options that apply and provide detail as needed; if yes, please attach drawing.*

- Seamed Edges  Yes  No \_\_\_\_\_
- Flat Machine Polished Edges  Yes  No \_\_\_\_\_
- Notches  Yes  No \_\_\_\_\_
- Internal Cutouts  Yes  No \_\_\_\_\_
- Pattern Cuts  Yes  No \_\_\_\_\_
- ANSI Logo on glass\*  Yes  No \_\_\_\_\_
- Holes  Yes  No \_\_\_\_\_

*\*ANSI Logo required for elevator interiors.*

**DESIGN CHARACTERISTICS**

Please choose **one** option from each category.

**Finish**

- Standard
- Pearlex+\*

**Transparency**

- Reflect
- View

**Magnetic**

- Magnetic
- Non-magnetic

\*Finish is available on one or two sides of double-sided View configurations. Please select one option below if you have a double-sided View configuration.

- One Side
- Two Sides

**HARDWARE OPTIONS**

Please choose all desired options and provide detail as needed.

**Slot Mount Standoff**

Finish

- Polished Brass
- Polished Chrome
- Polished Gun Metal
- Satin Chrome
- Satin Stainless Steel

Quantity: \_\_\_\_\_  
 Comments: \_\_\_\_\_

**Edge Grip Standoff**

Finish

- Polished Brass
- Polished Chrome
- Polished Gun Metal
- Satin Chrome
- Satin Stainless Steel

Quantity: \_\_\_\_\_  
 Comments: \_\_\_\_\_

**Round Standoff**

Standoff Base Length

- 1/4" (6.3 mm)
- 1/2" (12.7 mm)
- 3/4" (19.1 mm)
- 1" (25.4 mm)
- 1-1/2" (38.1 mm)
- 2" (50.8 mm)
- 4" (101.6 mm)
- 6" (152.4 mm)

Finish

- Polished Brass
- Polished Gun Metal
- Polished Stainless Steel
- Satin Stainless Steel
- Satin Chrome
- Polished Chrome

Quantity: \_\_\_\_\_  
 Comments: \_\_\_\_\_

**Spider Fitting**

Configuration

- 1-Arm
- 2-Arm
- 3-Arm
- 4-Arm

Finish

- Polished Stainless Steel
- Satin Stainless Steel

Quantity: \_\_\_\_\_  
 Comments: \_\_\_\_\_

**Square Mall Clamp**

Finish

- Polished Brass
- Polished Stainless Steel
- Satin Stainless Steel

Quantity: \_\_\_\_\_  
 Comments: \_\_\_\_\_

**Tapered Rail**

Finish

- Polished Brass
- Polished Stainless Steel
- Satin Stainless Steel
- Satin Anodized
- Black Bronze Anodized
- Black Powdercoat

Quantity: \_\_\_\_\_  
 Length: \_\_\_\_\_  
 Comments: \_\_\_\_\_

