

PROJECT NAME: _____ DATE: _____

JOB LOCATION: _____ SPECIFIER: _____

PLEASE USE ADOBE READER OR ADOBE ACROBAT TO FILL OUT AND SAVE FORM. USING OTHER PROGRAMS COULD RESULT IN UNSAVED DATA.

APPLICATIONS

Please select an option below to describe the end use for your glass. If selecting an F+S System application, please complete the corresponding System's Design Guide.

Forms+Surfaces Systems

- LEVELr Wall Cladding System
- LEVELr Column System
- LEVELe Wall Cladding System
- LEVELe Column System
- LEVELe Elevator Interiors
- LEVELc-2000 Elevator Interiors

- Glass Doors
- Stile & Rail Doors
- LightPlane Panels (View only)

Other Applications

- Loose Lite(s)
- Other: _____

Notes _____

For all ViviStone glass projects, please make selections from each of the following categories:

GLASS CHARACTERISTICS

Please choose **one** option from each category.

Configuration

- View*
- Reflect

Slab & Slab Number(s)

- Abalone Onyx, Slab # _____
- Cream Onyx, Slab # _____
- Honey Onyx, Slab # _____
- Opal Onyx, Slab # _____
- Pearl Onyx, Slab # _____
- White Onyx, Slab # _____

Finish

- Pearlex+
- Standard

*View configuration will be built one side selected finish / one side Standard finish (unless otherwise indicated in the project details).

PROCESSING REQUIREMENTS

Please choose **all** options that apply and provide detail as needed.

Cuts

- Notches* Yes No _____
- Internal Cutouts* Yes No _____
- Pattern Cuts* Yes No _____
- Holes* Yes No _____

ANSI

- ANSI logo on glass** Yes No _____
- ANSI logo type American Canadian _____
- ANSI logo placement Standard Custom*** _____

*If yes, please attach drawing.

**ANSI logo is required for elevator interiors.

***If ANSI logo placement is custom, please provide details.

For ViviStone glass projects used in "Other Applications", please also supply the following information:

LITE DESCRIPTION		
Description (include part number, if available)	Quantity	Size (width x height)
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

Notes _____

PROJECT DETAILS

Please choose **one** option from each category.

Installation Type <input type="checkbox"/> Captured Top & Bottom Only <input type="checkbox"/> Fully Framed <input type="checkbox"/> Mounted to a Solid Substrate <input type="checkbox"/> Curtain Wall/IGU <input type="checkbox"/> Post Mounted with Holes <input type="checkbox"/> Water Feature	Glass Thickness <input type="checkbox"/> 5/16" (7.7mm) <input type="checkbox"/> 7/16" (11.1mm) <input type="checkbox"/> 9/16" (13.7mm)	Environment <input type="checkbox"/> Interior, Standard Humidity <input type="checkbox"/> Interior, High Humidity <input type="checkbox"/> Exterior, Exposed Setting <input type="checkbox"/> Exterior, Covered Setting	Lighting Conditions <input type="checkbox"/> Natural <input type="checkbox"/> Backlit <input type="checkbox"/> Spotlight <input type="checkbox"/> Other (please provide details): _____ _____ _____
--	--	--	---

PROCESSING REQUIREMENTS

Please choose **all** options that apply and provide detail as needed.

Edges

Seamed Edges	<input type="checkbox"/> All Edges	<input type="checkbox"/> Top	<input type="checkbox"/> Bottom	<input type="checkbox"/> Left Side	<input type="checkbox"/> Right Side
Flat Machine Polished Edges	<input type="checkbox"/> All Edges	<input type="checkbox"/> Top	<input type="checkbox"/> Bottom	<input type="checkbox"/> Left Side	<input type="checkbox"/> Right Side

GLASS SAFETY STANDARDS

Please choose **one** option.

Safety Standards

Annealed

Tempered*

Heat Strengthened**

*Tempering is required for load bearing holes and cutouts. Please note that 5/16" laminated glass can only be tempered to a max of 47" x 80".
 **Heat strengthening is recommended for glass over 50 square feet.

Please send completed forms to sales@forms-surfaces.com or contact us at 800.451.0410 with any questions.