

PROJECT NAME: \_\_\_\_\_ DATE: \_\_\_\_\_

JOB LOCATION: \_\_\_\_\_ SPECIFIER: \_\_\_\_\_

PLEASE USE ADOBE READER OR ADOBE ACROBAT TO FILL OUT AND SAVE FORM. USING OTHER PROGRAMS COULD RESULT IN UNSAVED DATA.

**APPLICATIONS**

If you select a Forms+Surfaces System, please skip the Installation Type, Project Details, Lite Descriptions and Glass Characteristics sections.

**Forms+Surfaces Systems**

- Glass Doors
- LEVELe Wall Cladding System
- LEVELr Wall Cladding System
- LEVELr Column System
- LEVELe Column System
- LEVELc-2000 Elevator Interiors
- LEVELe Elevator Interiors

**Other Applications\***

- Loose Lite(s)
- Other \_\_\_\_\_

\*For Other Applications, please fill out all sections.

**INSTALLATION TYPE**

- Captured Top & Bottom Only
- Fully Framed
- Mounted to a Solid Substrate
- Curtain Wall/IGU
- Post Mounted with Holes
- Water Feature

**PROJECT DETAILS**

Please choose **one** option from each category.

**Environment**

- Interior, Standard Humidity
- Interior, High Humidity

**Lighting Conditions**

- Natural
- Backlit
- Spotlight
- Other (please provide details): \_\_\_\_\_

**Glass Thickness**

- 5/16" (7.7 mm)
- 7/16" (11.1 mm)
- 9/16" (13.7 mm)

**LITE DESCRIPTION**

Description (include part number, if available)	Quantity	Size (width x height)
_____	_____	_____
_____	_____	_____
_____	_____	_____

**GLASS CHARACTERISTICS**

Please choose one option from each category.

**Safety Standards**

- Annealed
- Tempered\*
- Heat Strengthened\*\*

If Tempered or Heat Strengthened glass is selected, please provide reason: \_\_\_\_\_

**Profile**

- Flat
- Curved (please attach drawing)

\*Tempering is required for load bearing holes and cutouts. Please note that 5/16" laminated glass can only be tempered to a max of 47" x 80"

\*\*Heat strengthening is recommended for glass over 50 square feet.

**PROCESSING REQUIREMENTS**

Please choose all options that apply and provide detail as needed; if yes, please attach drawing.

- Seamed Edges  Top  Bottom  Left Side  Right Side
- Flat Machine Polished Edges  Top  Bottom  Left Side  Right Side

- ANSI Logo on glass\*\*  Yes  No
- If ANSI Logo is needed  American  Canadian
- ANSI Logo placement  Standard  Custom\*\*\*

- Notches\*  Yes  No \_\_\_\_\_
- Internal Cutouts\*  Yes  No \_\_\_\_\_
- Pattern Cuts\*  Yes  No \_\_\_\_\_
- Holes\*  Yes  No \_\_\_\_\_

\*\*ANSI logo is required for elevator interiors.

\*\*\*If ANSI logo placement is custom, please provide detail.

\*If yes for any of the above options, please attach drawing.

STANDARD FINISHES

Please choose **one** finish option below.

Finish

- Standard
- Pearlex+\*


STANDARD PATTERNS

Please choose **one** pattern option below.


Abaca (shown in White)




Abaca (shown in Black)




Interlace (shown in White)




Interlace (shown in Black)



Lattice (shown in White)




Lattice (shown in Black)




Strand (shown in White)




Strand (shown in Black)



Understitch (shown in White)



Understitch (shown in Black)



**HARDWARE OPTIONS**

Please choose all desired options and provide detail as needed.

**Slot Mount Standoff**

Finish

- Polished Brass       Polished Chrome       Satin Chrome  
 Polished Gun Metal       Satin Stainless Steel

Quantity: \_\_\_\_\_

Comments: \_\_\_\_\_

**Edge Grip Standoff**

Finish

- Polished Brass       Polished Chrome       Satin Chrome  
 Polished Gun Metal       Satin Stainless Steel

Quantity: \_\_\_\_\_

Comments: \_\_\_\_\_

**Round Standoff\***

Standoff Base Length

- 1/4" (6.3 mm)       1/2" (12.7 mm)  
 3/4" (19.1 mm)       1" (25.4 mm)  
 1-1/2" (38.1 mm)       2" (50.8 mm)  
 4" (101.6 mm)       6" (152.4 mm)

Finish

- Polished Brass       Polished Stainless Steel       Satin Chrome  
 Polished Gun Metal       Satin Stainless Steel       Polished Chrome

Quantity: \_\_\_\_\_

Comments: \_\_\_\_\_

\*Requires tempered glass

**Spider Fitting\***

Configuration

- 1-Arm       3-Arm  
 2-Arm       4-Arm

Finish

- Polished Stainless Steel       Satin Stainless Steel

Quantity: \_\_\_\_\_

Comments: \_\_\_\_\_

\*Requires tempered glass

**Square Mall Clamp**

Finish

- Polished Brass       Polished Stainless Steel       Satin Stainless Steel

Quantity: \_\_\_\_\_

Comments: \_\_\_\_\_

**Tapered Rail**

Finish

- Polished Brass       Satin Stainless Steel       Black Bronze Anodized  
 Polished Stainless Steel       Satin Anodized       Black Powdercoat

Quantity: \_\_\_\_\_

Length: \_\_\_\_\_

Comments: \_\_\_\_\_

Please send completed forms to [sales@forms-surfaces.com](mailto:sales@forms-surfaces.com) or contact us at **800.451.0410** with any questions.

**NOTES**

---



---



---



---



---



---